

压差开关

Differential Pressure Switch



技术数据 Technical data

Model/型号	CRPD-S3	CRPD-H30	CRPD-S7
Temperature/环境温度	-20℃~80℃		
Electrical Specification/ 电气特性	3A.SPDT@ 250VAC和 28VDC	1A.SPDT@ 125VAC和 14VDC	3A.SPDT@ 250VAC和28VDC
Repeatability/重复性	It is 2% of the max. setting value when the temperature is 20℃. 在20℃时，为最高设定值的2%		
Transmission value/发讯值	△P=1bar~5bar (option 可选)	△P=1bar~8bar (option 可选)	△ P=1bar~5bar (option 可选)
Hosing material / 外壳材质	Aluminum Alloy/铝合金	Stainless Steel/不锈钢	
Pressure-proof / 耐压	31.5Mpa		
Electrical Connection / 气电连接	IP65 DIN43650		
Procedure Connection / 过程连接	7/8” ~14 M22*1.5 G1/2” (option 可选)	M20*1.5 ES30	M14-1.5
Media-Wetted Seal Material 与液体接触密封材质	(NBR) -40℃~120℃ ； (VITON) -20℃~200℃ ； (EPDM) -55℃~150℃ Special Material Optional/特殊材质可选		
Dimension/外形尺寸	54*30*10mm	85*34*92mm	81*45*30mm
Weight/重量	0.12kg	0.18kg	0.35kg

* Other Products and specification please contact us/其它产品和规格请洽我司