

# Connector 連接器

## A type



### Technical Features/技術資訊

		
Contact spacing/接點間距	18 mm	
Rated voltage /額定電壓	250 VAC/300 VDC	
Operating current/工作電流	10 A	
Max. current/最大電流	16 A	
Max. wire gauge/最大線規	1.5 mm <sup>2</sup>	
Cable gland/電纜接頭	PG9 / PG11	
Cable diameter/電纜外徑	6-8 mm	
Protection class/防護等級	IP65 (EN 60529)	
Housing material / 外殼材質	PA+30%GF	PA
Contact material/接點材質	CuZn (Ag)	
Screw/螺絲	M3	
Temperature range/溫度範圍	-40 °C to +125 °C	-30 °C to +90 °C

### Order information/訂購資訊

透明附指示燈

GDA 3 Y  9 0 T 2 2

**Pole**

3 : 3 PIN  
4 : 4 PIN

**Voltage/電壓**

Y : DC 24V  
R : AC110V/220V

**Varistor/突波器**

None : No  
V : Yes

**Cable gland/電纜外徑**

9 : PG 9  
1 : PG 9

黑殼

GDA 3 0 9 0 S 6 1

**Pole**

3 : 3 PIN  
4 : 4 PIN

**Cable gland/電纜外徑**

9 : PG 9  
1 : PG 9

**Gasket/墊片**



1 : Profile  
2 : Flat

# Connector 連接器

## B type



### Technical Features/技術資訊

		
Contact spacing/接點間距	10 mm (DIN/EN-德規) / 11 mm (Industrial-標準)	
Rated voltage /額定電壓	250 VAC/300 VDC	24 V
Operating current/工作電流	6A	
Max. current/最大電流	10A	
Max. wire gauge/最大線規	1.5 mm <sup>2</sup>	
Cable gland/電纜接頭	PG9	
Cable diameter/電纜外徑	6-8 mm	
Protection class/防護等級	IP65 (EN 60529)	
Housing material / 外殼材質	PA+30%GF	PA
Contact material/接點材質	CuZn (Ag)	
Screw/螺絲	M3	
Temperature range/溫度範圍	-40 °C to +125 °C	-30 °C bis +90 °C

### Order information/訂購資訊

透明附指示燈	黑殼
<p><b>G I B 3 Y</b> <span style="border: 1px solid black; display: inline-block; width: 15px; height: 15px; vertical-align: middle;"></span> <b>9 0 T 2 2</b></p> <p><b>Contact spacing/接點間距</b> I : 11 mm D : 10 mm</p> <p><b>Pole</b> 3 : 3 PIN</p> <p><b>Voltage/電壓</b> Y : DC 24V R : AC110V/220V</p> <p><b>Varistor/突波器</b> None : No V : Yes</p> <p><b>Cable gland/電纜外徑</b> 9 : PG 9</p>	<p><b>G I B 3 0 9 0 S 6 1</b></p> <p><b>Contact spacing/接點間距</b> I : 11 mm D : 10 mm</p> <p><b>Pole</b> 3 : 3 PIN</p> <p><b>Cable gland/電纜外徑</b> 9 : PG 9</p> <p><b>Gasket/墊片</b> 1 : Profile 2 : Flat</p>

# Connector 連接器

## C type



### Technical Features/技術資訊

		
Contact spacing/接點間距	8 mm (DIN/EN-德規) / 9.4 mm (Industrial-標準)	
Rated voltage /額定電壓	250 VAC/300 VDC	24 V
Operating current/工作電流	6 A	
Max. current/最大電流	10 A	
Max. wire gauge/最大線規	0.75 mm <sup>2</sup>	
Cable gland/電纜接頭	PG 7	
Cable diameter/電纜外徑	4-6 mm	
Protection class/防護等級	IP65 (EN 60529)	
Housing material / 外殼材質	PA+30%GF	PA
Contact material/接點材質	CuZn (Ag)	
Screw/螺絲	M2.5 (DIN/EN-德規) / M3 (Industrial-標準)	
Temperature range/溫度範圍	-40 °C to +125 °C	-30 °C bis +90 °C

### Order information/訂購資訊

