

IMPULSE TEST STAND BI703 FLEX

脉冲测试机 BI703 FLEX



SINCERT



BI703 FLEX is a machine for impulse test of hydraulic rubber flexible hoses static or with flexion and rotation.

BI703 FLEX主要为液压橡胶油管静态或曲折、旋转的脉冲测试机器。

Technical Features/技术信息

| | |
|--------------------------------------|---|
| Hoses under test/软管测试 | Max 4 at 90° - Max 6 at 180° |
| Max test pressure/最大测试压力 | 700 bar (10,150 psi) |
| Min test pressure/最小测试压力 | 50 bar (725 psi) |
| Displacement per impulse/每次脉冲排量 | 485 cm ³ (29.6 inch ³) |
| Max test frequency/最大测试频率 | 0,05 – 1,5 Hz. |
| Max oil temperature/最高油温 | 150° C (302° F) |
| Max distance between manifold/最大歧管间距 | 1850 mm (72") |
| Safety Devices / 安全装置 | <ul style="list-style-type: none"> - Emergency push button/紧急按钮 - Window equipped with Safety Glass and Wire Mesh/窗口配备安全玻璃和线网 - Interlock avoids to run the test with open doors/安全锁避免测试时机门开启 - Automatic stoppage in case of or malfunctioning/故障时自动停机 |
| Power Supply / 电源供应 | |
| -Industrial cooling water/工业冷却水 | T ≤ 20°C (68° F) |
| -Electrical Standard Supply/标准 | 400 V – 50 Hz. – 74 kVA |
| Dimensions / 尺寸 | 4.000 (158") x 1.780 (70") x 2.600 (102") (l, d, h) |
| Weight / 重量 | Net test stand weight 4000 kg (8900 lbs) |

*Technical specifications can be changed without notice/技术规格可不事先通知而变动

*The details or other specifications, please contact us! / 详细细节或其它规格机器，请洽我司!